		Number of Crew Members:				
		Mower #1:		Mower #2:	Weight:	
Name: Company Name:		veight.			_Weight:	
Email:		What type of work do you do				
Address:		When do you need this track!				
Phone Number:			Do you need help with financing?			
Website:		What is your current vehicle:				
Desired Cargo:		Is this a replacement truck or an additional truck?				
Estimated Cargo '	Weight:	Do you have a trade	vilat kilid:			
<u>Series:</u>						
□ Eco	□ Pro □	Fast Track	Open Body	☐ Dump Body	□ Contractor	
8						
Isuzu Chassis:	WB G	SVW	WB	GVW	WB GVW	
□ Isuzu G	<u></u>		el Single Cab		el Single Cab	
		□ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □				
- Out of the second						
Isuzu Chassis Op				•	ome Wheel Simulators	
		Block Heater	☐ Chrome Grill	☐ Back-Up Alarm ☐ Fire	=	
☐ Engine Oil Alert ☐ Heated Mirrors ☐ Tinted Windows ☐ Back-Up Camera ☐ Seat Covers ☐ Safety Light upgrade						
Bodies:	SLT Pro Series Package:	SLT Basic Box with	Open Landscape Body:	Dump Body:	Contractor Enclosed Body:	
SLT Eco Series:	Dumper and Enclosed Body:	Rear Roll-Up Door	: □ 16' Open Body	☐ 2' X 96" I-Pack Toolbox	□4' Contractor Body	
☐ 12' Eco Body		☐ 12' Basic Body	☐ 18' Open Bod	□12' Dump Body	☐6' Contractor Body	
☐ 14' Eco Body	☐ 5.0 Cu Yd Debris Bin	☐ 14' Basic Body	□ 20' Open Body	□ 14' Dump Body	□8' Contractor Body	
☐ 16' Eco Body	2.5 Debris Dumper	☐ 16' Basic Body	22' Open Body	□16' Dump Body	Dump Body:	
☐ 18' Eco Body	· ·			☐ 18' Dump Body	□8' Dump Body	
☐ 20' Eco Body	☐ 5.0 Debris Dumper	☐ 18' Basic Body	Open Body Options:	Rear Barn Doors		
□ 22' Eco Body	SLT Pro Enclosed Body:	☐ 20' Basic Body	☐ Weed Eater Rack		□ 10' Dump Body	
	□12' Pro Body □ 18' Pro Body	1,	☐ Water Cooler Rack	Fold Down Curbside	☐ 12' Dump Body	
☐ 2500 Eco Series	□14' Pro Body □ 20' Pro Body		☐ Blower Rack	☐ Fold Down Road Side		
☐ 4000 Eco Series	□16' Pro Body □ 22' Pro Body	' 	☐ Reinforced Ramp	□		
Enclosed Body Side Door Options: 36" Roll Up Door 48" Rollup Door C - Curbside						
☐ 36" Single Panel Swing Door ☐ 48" Single Panel Swing Door ☐ 48" Dual Panel R - Roadside						
☐ 60" Dual Panel Swinging Door ☐ Roll Up Hutch Door ☐ 36" X 36" Swing Hutch Door Locate From						
☐ 1 Step Entry ☐ 2 Step Entry ☐ Stirrup Step Entry Leading Edge from Wall						
Ramps:		· · · · · · · · · · · · · · · · · · ·	·	· · · · · · · · · · · · · · · · · · ·		
Pro Series Hydra Ramp: MR-750 Manual Ramp:						
Pro Series Hydra Ramp. ☐ HR 1500 (Used Truck) ☐ 2500 Pro Hydra Ramp						
_	_ ·		·			
□ 3500 Pro Hydra Ramp □ 4000 Pro Hydra Ramp □ 43.5″ MR-750 □ 48″ MR-750 □						
Dovetail Ramp:	Side Ramp:	C. cham	☐ Right Side	☐Left Side ☐	Both	
□ Doveta	ail Ramp SR 3200	Custom		rl		
<u>Fuel Stations:</u>		<u>Fuel</u>		<u>Fuel</u>	Fuel Type:	
	☐ 14 Gallon Fuel Dispensing No		26 Gallon Fuel Dispensing I		G - Gas	
	☐ 39 Gallon Fuel Dispensing No	ozzles ⊔	54 Gallon Fuel Dispensing I	Nozzles	D - Diesel	
					P - Pre-Mix	
<u>Underbody Tool</u>	boxes:					
24" Underbody Toolbox			□ 36" Underbody Toolbox □ Other			
	☐ 48" Underbody Toolbox		60" Underbody Tool Box	□Othe	er	
Enclosed Body A	ccessories:			☐ Surface Moun	ted D-Rings Qty:	
☐ Single Utility Shelf ☐ Interior Wood		Vood	☐ Double Utility Shelf ☐ D-Ring in Floors Qty:		rs Qty:	
☐ Air Compressor ☐ Louvre Ve		ents		☐ 1500 Watt Power Convertor		
. ☐ Hand and Powertool Storage System			☐ Irrigation Parts Bin ☐ E-Track			
Marketing Packa			<u> </u>			
☐ Four Sided Vinyl Graphics ☐ Changeable Fleet Graphics ☐ Rail System for Changeable Fleet Graphics						
☐ Custom Paint - Cab ☐ Custom Paint - Body ☐ Other:						
Towing Package, Tarp Covers & Special Step Access:						
☐ Heavy Duty Receiver Hitch with 7 Pin Plug and Brake ControllerTarp Cover for DumperPull out steps for Debris Dumper						
<u>Delivery:</u>		Will you be picking t	his up or do you need us to	deliver it to your door?		
	☐ Delivery to Atlanta Ha	rtsfield Airport \$		Deliver to Your Company	per mile	

Super Lawn Trucks Product Details and Descriptions

Eco Serie

SLT ECO[™] Body - Standard specifications - Dry Freight Aluminum (ADF) Typical nominal length <u>includes 2 foot interior dovetail</u> (sloped rear), 96" Wide Exterior (92 inch wide Interior) x 85" Interior Height, Galvaneal Steel Frame Under Structure Unpainted, 1 1/8 inch thick hardwood floor, translucent roof, ¾" thick interior plywood liner on walls 4' from floor, 4 hardwood slats above. Interior front wall ¾" plywood from ceiling to floor, one interior dome light with switch, .040 White Aluminum exterior, interior side Z-posts on 16 inch center,. Light package per FMVSS, 2 mud flaps, rear bumper guards, tag light - body mounted and installed on cab chassis, complete vehicle certification provided. <u>Options available</u>: side doors, louvre vents, undercoating or interior body coating for corrosion control.

Pro Series

Super Lawn Pro Series™- Body System standard specifications—Dry Freight Aluminum (ADF) Typical nominal length, flat floor throughout, No wheel wells no dovetail sloped area, -.040 Aluminum exterior, Flat floor - 96" Exterior Width (92" Interior Width) x 85" Interior Height - Galvaneal Steel Frame Under Structure Unpainted, 1 1/8 inch thick hardwood floor, translucent roof, ¾" thick interior plywood walls up 4 feet from floor, 4 hardwood slats above. White Aluminum exterior, interior side Z-posts on 16 inch center, Light package per FMVSS, 2 mud flaps, rear ICC bumper, tag light - body mounted and installed on cab chassis, complete vehicle certification provided. Options available: side doors, louvre vents, undercoating or interior body coating for corrosion control.

Open Landscape Bodies

Standard Specifications Landscape Body Nominal length includes, All steel construction, 96 inch wide exterior body, 4' Dovetail, Spring assist split loading ramp 60 inches long, ramp covered with expanded metal to reduce weight, 60" height Headboard with 24 inch by 24 inch lockable storage basket (expanded metal construction) and Extra Shelf, located behind headboard, 16" Height Sides, Passenger Side Fold Down, Black in Color. <u>Additional options include:</u> 3 unit or 4 unit Trimmer Rack, 4 unit or 8 unit Shovel Rack, Water Cooler Rack, Reinforced Ramps, Reinforced Floor, Body Color Change, Additional Fold Down Side, Blower rack, Towing Package.

Debris Dumper

Standard Specifications Debris Dumper ™, All steel construction, **2.5 Cubic Yard Dimensions 80" Wide x 48" H eight x 36" Length**, Dual Half Swing Doors Both Sides., Dumps to Passenger Side, Black in Color, Approximately 1 Ton Lift Rating, 8 D-Rings for Tarp Tie Down, Hoist controlled by 12volt DC electric over hydraulic power unit, Dump controls located exterior of cab behind the dump unit, **Optional Specifications**: **5.0 Cubic Yard Dimensions 88" Wide x 60" H eight x 48" Length**, Tarp cover with tie downs, Slide Out Step for Debris Dumper, Solid Piece, No Moving Parts for All Gas Trucks and Diesel Crew Cabs Only, OR Slide Out Folding Steps for Debris Dumper, Fold Down Double Step with Pins for All Trucks (required specification on all diesel sing le cab trucks).

2.5 Cubic Yard Debris Bin (Non-Dumping) - All steel construction. 80"W x 48"H x 36" L, Dual Half swing doors each side, black in color.

5.0 Cubic Yard Debris Bin (Non-Dumping) - All steel construction. 88"W x 60"H x 48" L, Dual Half swing doors each side, black in color.

Contractor Truck

SLT Contractor Truck combines a rear mounted dumping unit nominal length PLUS a forward mounted Aluminum Dry Freight (ADF) enclosed body nominal length, side entry door required with this design, Nominal Length ADF Options 4, 6, 8 or 10 feet Flat Floor, 96 inch Exterior Width x 85 inch Interior Height, Galvaneal Steel Frame Under Structure Unpainted, 1 1/8 inch thick hardwood floor, translucent roof, interior plywood walls 24" from floor, 8 slats Above, .040Aluminum Exterior, White in Color.

Rear mounted contractor dump standard specifications, all steel construction, Nominal length, 96 inches wide, 60 inch headboard, 30 inch high sides, curbside folds down, rear barn doors 30 inch height, Light package per FMVSS, 2 mud flaps, rear ICC bumper, tag light - body mounted and installed on cab chassis, complete vehicle certification provided.

Enclosed Body Side Door Options:

All door locations measured from the front wall to the leading edge of door frame, <u>Single Panel Swing Door</u> 36 inch or 48 inch wide, All door hardware galvanized steel, door hardware to accommodate pad lock NOT SUPPLIED with door, Single Door Swings to Front of Body, Stirrup Step and Grab Handle Entry. <u>Dual Swinging Side Doors</u>—for 48 inch, 60 inch, 72 inch or 96 inch widths, opens from the middle, All door hardware galvanized steel, door hardware to accommodate pad lock NOT SUPPLIED with door, Stirrup Step with Interior Mounted Grad Handle Entry. <u>People Entry Side Door</u> - Aluminum Roll-up Side Door with two step pedestrian entry, locate grab handle exterior of door,

Ramps

Eco Series Hydra Ramp: Only available with SLT Eco Series enclosed body - all steel construction, electric over hydraulic, push button controls mounted in locking toolbox, antislip coating on the ramp face, ramp serves as rear door for truck body, black paint on ramp bottom—2500 pound weight rating

<u>Pro Series Hydra Ramp</u>: 2 Piece Folding Ramp, Dual Lever Controlled, Dual Hydraulic Cylinder, All Steel Construction, Anti Slip Coating, Ramp Serves as Rear Door, Black in Color—available with 2500, 3500, or 4000 pound weight rating

Exterior Dove Tail: 4 ft exterior dovetail, solid steel construction, with 6' manual fold down split ramp, coil spring assist, expanded metal on fold down portion, anti-slip coating on checker plate steel on dovetail ramp, black in color

MR-750 Manual Ramp: exterior mounted bi-fold ramp, solid steel frame with expanded metal face, dual gas shock assist, black in color - DETERMINE SIZE NEEDED Nominal width per ramp - 10 ft long - designed for dry freight or flat bed bodies. 30 inches to 40 inch finished floor height.

Fuel Tanks

Fuel Transport Tanks with Fuel Dispensing Nozzles (5gpm regular gas - 0.75gpm premix) Electric Pumps with Master Kill Switch in Cab, Externally Mounted, Drain Plug in Lower Right Back Corner - Located Road Side Forward of Drive Axle. All steel construction, labeled and installed on truck frame or under truck body.

Tool Boxes - All steel construction, nominal length x 18 inches x 18 inches, locking T-Handle, key lock, 90 degree door cables, powder coated black Underbody Toolbox nominal length 18" x 18" Locking T Handle, Water Resistant Seal, Wire Stops, Steel Construction, Powder coated Black.

Enclosed Body Accessories:

Single Utility Shelf - Steel Frame, Plywood Bottom, Locate Shelf 43" from Floor, shelf size (24¾" x 91¾")

Double Utility Shelf - Steel Frame, Plywood Bottom, Locate First Shelf 43" from Floor, Locate Second Shelf 64" from Floor (24%" x 91%")

1500 Watt Power Inverter - Low Voltage Audible Alarm, 3 120V Pluggins, Mounted on Wall Under Lower Shelf

Air Compressor (3 Gallon, 12V) with 25' Hose and Reel, 25' Extra Hose, Compressor Mounted on Driver Side Upper Shelf, Reel Mounted Driver Side Upper Rear Body Hand and Powertool Storage System - organizes over 30 hand and power tools on sidewall interior of enclosed truck bodies - Steel Contructions

Marketing Packages

4 Sided Vinyl Graphics - Includes Front & Rear Graphics

Changeable Fleet Graphics - includes 1 billboard design, 2 banners, front & rear graphics

Rail System for Removable Fleet Graphics - Rails to hang graphics