


Date: _____
Name: _____
Company Name: _____
Email: _____
Address: _____
Phone Number: _____
Website: _____
Desired Cargo: _____
Estimated Cargo Weight: _____

Number of Crew Members: _____
Mower #1: _____ Weight: _____ Mower #2: _____ Weight: _____
Mower #3: _____ Weight: _____ Other: _____ Weight: _____
What type of work do you do?: _____
When do you need this truck? _____
Do you need help with financing? _____
What is your current vehicle? _____ Do you have any Isuzu trucks? _____
Is this a replacement truck or an additional truck? _____
Do you have a trade-in? _____ What kind? _____

Series:

☐ Eco ☐ Fast Track ☐ Open Landscape ☐ Dump Body ☐ Contractor ☐ Solar

 **Isuzu Chassis:** WB GVW WB GVW
☐ Isuzu Gas Single Cab _____ ☐ Isuzu Diesel Single Cab _____
☐ Isuzu Gas Crew Cab _____ ☐ Isuzu Diesel Crew Cab _____

Bodies:

SLT Eco Series:

- ☐ 12' Eco Body
- ☐ 14' Eco Body
- ☐ 16' Eco Body
- ☐ 18' Eco Body
- ☐ 20' Eco Body
- ☐ 22' Eco Body

SLT Eco Series Package:

Debris Dumper:

- ☐ 2.5 CY Debris Dumper
- ☐ 5.0 CY Debris Dumper
- ☐ DD Lid
- ☐ DD Tarp
- ☐ Pullout Steps
- Ramps:**
 - ☐ 2500 lb Eco Series
 - ☐ 4000 lb Eco Series

SLT Morgan with

Rear Roll-Up Door:

- ☐ 12' Morgan Body
- ☐ 14' Morgan Body
- ☐ 16' Morgan Body
- ☐ 18' Morgan Body
- ☐ 20' Morgan Body
- ☐ 22' Morgan Body
- ☐ Other: _____

Open Landscape Body:

- ☐ 16' Open Body
- ☐ 18' Open Body
- ☐ 20' Open Body
- ☐ 22' Open Body
- Open Body Options:**
 - ☐ Weed Eater Rack
 - ☐ Water Cooler Rack
 - ☐ Blower Rack
 - ☐ Reinforced Ramp
 - ☐ Shovel Rack
 - ☐ Headboard / Basket

Dump Body:

- ☐ 2' X 96" I-Pack Toolbox
- ☐ 12' Dump Body
- ☐ 14' Dump Body
- ☐ 16' Dump Body
- ☐ 18' Dump Body
- ☐ Rear Barn Doors
- ☐ Fold Down Curbside
- ☐ Fold Down Road Side
- ☐ _____

Contractor Enclosed Body:

- ☐ 4' Contractor Body
- ☐ 6' Contractor Body
- ☐ 8' Contractor Body
- ☐ 10' Contractor Body
- Dump Body:**
 - ☐ 8' Dump Body
 - ☐ 10' Dump Body
 - ☐ 12' Dump Body

Enclosed Body Side Door Options:

- ☐ 36" Single Panel Swing Door _____
- ☐ 60" Dual Panel Swinging Door _____
- ☐ 1 Step Entry _____

☐ 36" Roll Up Door _____

- ☐ 48" Single Panel Swing Door _____
- ☐ Roll Up Hutch Door _____
- ☐ 2 Step Entry _____

☐ 48" Rollup Door _____

- ☐ 48" Dual Panel _____
- ☐ 36" X 36" Swing Hutch Door _____
- ☐ Stirrup Step Entry _____

C - Curbside
R - Roadside
Locate _____ From
Leading Edge from Wall

Contractor Truck Options:

Enclosed Body Options:

- ☐ Rollup Door with Stirrup Step
- ☐ SR3200 ☐ 48" ☐ 60" ☐ SR1600

Dump Body Options:

- ☐ Aluminum Frame / Composite
- ☐ Steel
- ☐ 30" Dump Bed Extensions
- ☐ Manual Tarping System
- ☐ Extended Mirror Package
- ☐ Dual Cameras
- ☐ MR-750 Mounted
- ☐ Custom Paint
- ☐ Safety Cone Holder

Fuel Stations:

- ☐ 14 Gallon Fuel Dispensing Nozzles _____
- ☐ 39 Gallon Fuel Dispensing Nozzles _____
- ☐ 26 Gallon Fuel Dispensing Nozzles _____
- ☐ 54 Gallon Fuel Dispensing Nozzles _____

Fuel Type:
G - Gas
D - Diesel
P - Pre-Mix

Underbody Toolboxes:

- ☐ 24" Underbody Toolbox
- ☐ 48" Underbody Toolbox
- ☐ 36" Underbody Toolbox
- ☐ 60" Underbody Tool Box
- ☐ Other _____
- ☐ Other _____

Enclosed Body Accessories:

- ☐ Single Utility Shelf
- ☐ Air Compressor
- ☐ Tool Storage System
- ☐ 2000 Watt Inverter
- ☐ Extra Battery
- ☐ Interior Wood
- ☐ Louvre Vents
- ☐ Step Well Cover
- ☐ LED Strip Lighting
- ☐ Back-Up Alarm
- ☐ Double Utility Shelf
- ☐ Epoxy Coating Interior
- ☐ Irrigation Parts Bin
- ☐ Chrome Wheel Simulators
- ☐ Back-Up Camera
- ☐ D-Ring in Floors Qty: _____
- ☐ E-Track _____
- ☐ Safety Light Package

Marketing Packages:

- ☐ Four Sided Vinyl Graphics
- ☐ Custom Paint - Cab
- ☐ Changeable Fleet Graphics
- ☐ Custom Paint - Body
- ☐ Rail System for Changeable Fleet Graphics
- ☐ Aluminum Skin for Side Ramp

Towing Package:

- ☐ Heavy Duty Receiver Hitch with 7 Pin Plug and Brake Controller

Delivery:

- ☐ Delivery to Atlanta Hartsfield Airport
- ☐ Deliver to Your Company
- ☐ Pick-up at SLT

Financing:

- ☐ No Financing
- ☐ Financing thru own Bank
- ☐ Isuzu Loan
- ☐ Isuzu Lease

Super Lawn Trucks Product Details and Descriptions

Eco Series

SLT ECO™ Body - Standard specifications - Dry Freight Aluminum (ADF) Typical nominal length **includes 2 foot interior dovetail** (sloped rear) , 96" Wide Exterior (92 inch wide Interior) x 85" Interior Height, Galvaneal Steel Frame Under Structure Unpainted, 1 1/8 inch thick hardwood floor, translucent roof, 3/4" thick interior plywood liner on walls 4' from floor, 4 hardwood slats above. Interior front wall 3/4" plywood from ceiling to floor, one interior dome light with switch, .040 White Aluminum exterior, interior side Z-posts on 16 inch center,. Light package per FMVSS, 2 mud flaps, rear bumper guards, tag light - body mounted and installed on cab chassis, complete vehicle certification provided. **Options available:** side doors, louvre vents, undercoating or interior body coating for corrosion control.

Pro Series

Super Lawn Pro Series™- Body System standard specifications—Dry Freight Aluminum (ADF) Typical nominal length, flat floor throughout, No wheel wells no dovetail sloped area, -.040 Aluminum exterior, Flat floor - 96" Exterior Width (92" Interior Width) x 85" Interior Height - Galvaneal Steel Frame Under Structure Unpainted, 1 1/8 inch thick hardwood floor, translucent roof, 3/4" thick interior plywood walls up 4 feet from floor, 4 hardwood slats above. White Aluminum exterior, interior side Z-posts on 16 inch center, Light package per FMVSS, 2 mud flaps, rear ICC bumper, tag light - body mounted and installed on cab chassis, complete vehicle certification provided. **Options available:** side doors, louvre vents, undercoating or interior body coating for corrosion control.

Open Landscape Bodies

Standard Specifications Landscape Body Nominal length includes, All steel construction, 96 inch wide exterior body, 4' Dovetail, Spring assist split loading ramp 60 inches long, ramp covered with expanded metal to reduce weight, 60" height Headboard with 24 inch by 24 inch lockable storage basket (expanded metal construction) and Extra Shelf, located behind headboard, 16" Height Sides, Passenger Side Fold Down, Black in Color. **Additional options include:** 3 unit or 4 unit Trimmer Rack, 4 unit or 8 unit Shovel Rack, Water Cooler Rack, Reinforced Ramps, Reinforced Floor, Body Color Change, Additional Fold Down Side, Blower rack, Towing Package.

Debris Dumper

Standard Specifications Debris Dumper™, All steel construction, **2.5 Cubic Yard Dimensions 80" Wide x 48" H eight x 36" Length**, Dual Half Swing Doors Both Sides., Dumps to Passenger Side, Black in Color, Approximately 1 Ton Lift Rating, 8 D-Rings for Tarp Tie Down, Hoist controlled by 12volt DC electric over hydraulic power unit, Dump controls located exterior of cab behind the dump unit, **Optional Specifications: 5.0 Cubic Yard Dimensions 88" Wide x 60" H eight x 48" Length**, Tarp cover with tie downs, Slide Out Step for Debris Dumper, Solid Piece, No Moving Parts for All Gas Trucks and Diesel Crew Cabs Only, OR Slide Out Folding Steps for Debris Dumper, Fold Down Double Step with Pins for All Trucks (required specification on all diesel sing le cab trucks).

2.5 Cubic Yard Debris Bin (Non-Dumping) - All steel construction. 80"W x 48"H x 36" L, Dual Half swing doors each side, black in color.

5.0 Cubic Yard Debris Bin (Non-Dumping) - All steel construction. 88"W x 60"H x 48" L, Dual Half swing doors each side, black in color.

Contractor Truck

SLT Contractor Truck combines a rear mounted dumping unit nominal length PLUS a forward mounted Aluminum Dry Freight (ADF) enclosed body nominal length, side entry door required with this design, Nominal Length ADF Options 4, 6, 8 or 10 feet Flat Floor, 96 inch Exterior Width x 85 inch Interior Height, Galvaneal Steel Frame Under Structure Unpainted, 1 1/8 inch thick hardwood floor, translucent roof, interior plywood walls 24" from floor, 8 slats Above, .040Aluminum Exterior, White in Color.

Rear mounted contractor dump standard specifications, all steel construction, Nominal length, 96 inches wide, 60 inch headboard, 30 inch high sides, curbside folds down, rear barn doors 30 inch height, Light package per FMVSS, 2 mud flaps, rear ICC bumper, tag light - body mounted and installed on cab chassis, complete vehicle certification provided.

Enclosed Body Side Door Options:

All door locations measured from the front wall to the leading edge of door frame, **Single Panel Swing Door** 36 inch or 48 inch wide, All door hardware galvanized steel, door hardware to accommodate pad lock NOT SUPPLIED with door, Single Door Swings to Front of Body, Stirrup Step and Grab Handle Entry . **Dual Swinging Side Doors**—for 48 inch , 60 inch , 72 inch or 96 inch widths, opens from the middle, All door hardware galvanized steel, door hardware to accommodate pad lock NOT SUPPLIED with door, Stirrup Step with Interior Mounted Grab Handle Entry. **People Entry Side Door** - Aluminum Roll-up Side Door with two step pedestrian entry , locate grab handle exterior of door,

Ramps

Eco Series Hydra Ramp: Only available with SLT Eco Series enclosed body - all steel construction, electric over hydraulic, push button controls mounted in locking toolbox, anti-slip coating on the ramp face, ramp serves as rear door for truck body, black paint on ramp bottom—2500 pound weight rating

Pro Series Hydra Ramp: 2 Piece Folding Ramp, Dual Lever Controlled, Dual Hydraulic Cylinder, All Steel Construction, Anti Slip Coating, Ramp Serves as Rear Door, Black in Color—available with 2500, 3500, or 4000 pound weight rating

Exterior Dove Tail: 4 ft exterior dovetail, solid steel construction, with 6' manual fold down split ramp, coil spring assist, expanded metal on fold down portion, anti-slip coating on checker plate steel on dovetail ramp, black in color

MR-750 Manual Ramp: exterior mounted bi-fold ramp, solid steel frame with expanded metal face, dual gas shock assist, black in color - DETERMINE SIZE NEEDED
Nominal width per ramp - 10 ft long - designed for dry freight or flat bed bodies. 30 inches to 40 inch finished floor height.

Fuel Tanks

Fuel Transport Tanks with Fuel Dispensing Nozzles (5gpm regular gas - 0.75gpm premix) Electric Pumps with Master Kill Switch in Cab, Externally Mounted, Drain Plug in Lower Right Back Corner - Located Road Side Forward of Drive Axle. All steel construction, labeled and installed on truck frame or under truck body.

Tool Boxes - All steel construction, nominal length x 18 inches x 18 inches, locking T-Handle, key lock, 90 degree door cables, powder coated black
Underbody Toolbox nominal length 18" x 18" Locking T Handle, Water Resistant Seal, Wire Stops, Steel Construction, Powder coated Black.

Enclosed Body Accessories:

Single Utility Shelf - Steel Frame, Plywood Bottom, Locate Shelf 43" from Floor, shelf size (24 3/4" x 91 3/4")

Double Utility Shelf - Steel Frame, Plywood Bottom, Locate First Shelf 43" from Floor, Locate Second Shelf 64" from Floor (24 3/4" x 91 3/4")

1500 Watt Power Inverter - Low Voltage Audible Alarm, 3 120V Pluggins, Mounted on Wall Under Lower Shelf

Air Compressor (3 Gallon, 12V) with 25' Hose and Reel, 25' Extra Hose, Compressor Mounted on Driver Side Upper Shelf, Reel Mounted Driver Side Upper Rear Body
Hand and Powertool Storage System - organizes over 30 hand and power tools on sidewall interior of enclosed truck bodies - Steel Contructions

Marketing Packages

4 Sided Vinyl Graphics - Includes Front & Rear Graphics

Changeable Fleet Graphics - includes 1 billboard design, 2 banners, front & rear graphics

Rail System for Removable Fleet Graphics - Rails to hang graphics